ASSA ABLOY Locker Hasp



Free Spinning Locker Hasp



Area of usage

ASSA ABLOY Locker Hasp for use on lockers, cabinets, boxes etc.

Performance

ASSA ABLOY Locker Hasp are available in two lengths. The shorter version is suitable for doors with thickness up to 15 mm and the long version for doors with thickness up to 22 mm.

Housing and core of zinc plated steel. Large selection of 3 mm thick catches. The Locker hasp has the same hole footprint as ASSA ABLOY Cylinder 10450/10460.

Function

In the locked position the handle is free spinning and the catch is locked from rotationg. This means that it is not possible to apply any torque into the lock.

In the open position the handle can be pressed in and the catch can then be turned 90 degrees, thus allowing for opening of the locker.

For optimal function we recommend pad locks that has a shackle with a diameter between 4.5 and 6 mm.


We reserve the right to correct any printing errors and update the information after printing.


ASSA ABLOY Locker Hasp




Free Spinning Locker Hasp

Dimensional sketch (mm). Dimension long version in brackets





Hole preparation



Article number

000118100 010 011 Right – Long version 000118100 020 011 Left – Long version 000447939 010 011 Right – Short version 000477939 020 011 Left – Short version

Article	Article number	Material	Surface Treatment
Big Nut	490610 000 057	Steel	Zinc Plated
Small Nut	491439 000 057	Steel	Zinc Plated
Washer	490246 000 057	Steel	Zinc Plated
Note			
Accessories	See "Accessories"		
Catches	See "Catches"		
Spare Parts	See "Spare Parts"		

ASSA ABLOY Opening Solutions Sweden P.O. Box 371 SE-631 05 Eskilstuna Sweden

Phone +46 (0)16 17 70 00 Fax +46 (0)16 17 70 49 Customer support:

Phone intl. +46 (0)16 17 71 00 Phone nat. 0771-640 640 Fax +46 (0)16 17 73 72 e-mail: helpdesk.se.openingsolutions@assaabloy.com www.assaabloyopeningsolutions.se